



J4

Assault rifle, LMG and DMR scope





Combat proven high performance rifle scope designed to enhance the rifleman and machine-gunner performances

APPLICATIONS & BENEFITS

TECHNICAL CHARACTERISTICS

A rifle scope designed for assault rifle, LMG or DMR, short range up to 600m.

Shooting performance range:



Reticles available: designed on request by Elynxo





KEY FEATURES

• User centric

Polyvalence: Its LED-backlit combat reticle and large light transmission make it possible to shoot in all conditions of close combat.

Qualitative

Optimised optical formula: Allowing great clarity, large exit pupil and exceptional eye relief.

Combat proven: In use by the French Armed Forces.

Designed and qualified for harsh environments: From desert to high mountains, our scope will support operational contraints in extreme environmental conditions.

Optical Performance:

Magnification	4 x 26.4mm
Field of view	5.1° - 9m at 100m
Ocular lens diameter	26.4 mm
Exit pupil	6 mm
Eye relief	70 mm
Reticule	MilDot or Ballistic
Parallax	Fixed, 300 m
Light transmission	> 90 %
Correction per click	0.2 mrad (2 cm at 100 m)
Vertical / Horizontal range	+/-8 mrad

Mechanical Data:

- Weight: 380g
- Dimensions: 187mm (L) x 61mm (H) x 62mm (W)
- Mechanical interfaces: Integrated STANAG 2324 / ringless

Environmental Characteristics:

- Operating temperature: -31°C / +51°C
- Storage temperature: -46°C / +70°C

Included:

- Transport suitcase
- Instruction manual
- Eye cup

On Request:

- Flip-up front and back lens covers
- Standard or fast-off STANAG 4694 adaptator
- Weapon rail adapter
- Honeycomb and anti-laser filters





4, avenue de l'Amazonie 91940 Les Ulis/France

T: +33 (0)1 46 74 11 19

E: sales@elynxo-group.fr www.elynxo-group.fr